

FM1010 Easy Plug & Play Tracker



Description

FM1010 is an easy plug and track realtime tracking terminal with GPS/GLONASS and GSM connectivity, which is able to collect device coordinates and other useful data to transfer them via GSM network to server. This device is perfectly suitable for applications where location acquirement of remote objects is needed: fleet management, carrental companies, taxi companies, personal cars and so on.

Applications







If You think, this is not enough to win ALL Your potential customers - please contact us to get advices how to use it in Your application!









Accessories/features





Internal backup battery



Trip detection



Overspeeding detection



Auto Geofencing



Detect car towing



Car theft prevention



Power saving



Features

- Plug and Track
- Small and easy to mount case directly to car OBDII connector
- Internal GSM antenna and Internal GPS/GLONASS antenna allow mount FM1010 much easier
- RealTime tracking
- Smart data acquisition based on time, distance, angle, ignition and I/O events allow to have precise online tracker
- Sending acquired data via GPRS (TCP/IP and UDP/IP protocols)
- Smart algorithm of GPRS connections for GPRS traffic saving
- Operating in roaming networks by preferred GSM providers list
- Events from I/O elements detection and sending via GPRS or SMS
- Scheduled 24 coordinates SMS sending when GPRS not available
- 5 geofence zones (rectangular or circle)
 - Auto Geofencing crested for cartowing detection and cartheft prevention
- Deep Sleep mode (less than 2 mA power consumption)
- FOTA (firmware updating via GPRS)
- 3 operational modes (Home, Roaming, Unknown) based on operator
- Integrated scenarios:
 - Over speeding to secure driver and prevent penalties
 - ☐ Trip start and end detection
- FM1010 supports a remote logs reading
 - FM1010 supports remote diagnostic logs functionality using GPRS. Possible issues resolving becomes faster. Manufacturer can read logs remotely using SMS/GPRS to diagnose the FM1010 and timely respond to the fault

Specification

GSM

- Quad-band 900/1800 MHz; 850/1900 MHz
- GPRS class 10 (up to 85,6 kbps)
- SMS (text/data)

GPS/GLONASS

- NMEA, GGA, GGL, GSA, GSV, RMC, VTG protocol compatible
- 32 channel GPS/GLONASS receiver
- Up to -161 dBm sensitivity

Interface

- 1 Digital Input Reserved for Ignition Status Monitoring (depends on vehicle type)
- Accelerometer
- Power supply (+10...+16) V DC
- Integrated back-up battery (optional)
- Internal High Gain GSM antenna
- Internal High Gain GPS/GLONASS antenna
- Dimensions: L(50,7mm)xW(49,6mm)xH(25mm)
- 2 Status LEDs
- Configuration and firmware upload (FOTA and via cable)



Accessories

USB to mini USB cable



FM1010 adapter for power connection not from OBDII connector



FM1010 adapter for power connection from cigarette lighter



If You think, this is not enough to win ALL Your potential customers - please contact us to get advices how to use it in Your application!

HQ JSC Teltonika Saltoniskiu str. 10C, LT-08105, Vilnius,Lithuania Phone: +370 5 2127472 Fax: +370 5 2761380 info@teltonika.lt

www.teltonika.lt